



# TOTALBOAT SPECIAL BRUSHING THINNER 100

- Improves flow and application properties
- Slow-drying reducing solvent
- Extends wet edge and working time
- Designed for TotalBoat finishes
- This product is specially formulated to be used exclusively for marine coatings

TotalBoat Special Brushing Thinner is a versatile brushing thinner that improves flow characteristics and slows drying to extend wet edge working time for specified TotalBoat coatings. It is also very effective for tool cleanup and as a surface preparation solvent wipe.

---

**PRODUCT APPLICATIONS:** Brushing/rolling. Special Brushing Thinner 100 can also be used for product cleanup and equipment/tool cleanup, as well as a surface preparation solvent wipe for compatible TotalBoat products.

**COMPATIBLE TOTALBOAT PRODUCTS:** TotalBoat Wet Edge, TotalBoat TotalTread, TotalBoat Topside Primer, TotalBoat TotalBilge, TotalBoat TotalGold, Gleam, TotalBoat Lust, TotalBoat Wood Sealer, TotalBoat Outdrive AF, Krypton, Alumipaint AF, TotalBoat Spartan, TotalBoat Underdog

**INCOMPATIBLE TOTALBOAT PRODUCTS:** JD Select, Aluminum Boat Topside Paint, Inflatable Boat Paint, 2-Part Epoxy Primers, TotalProtect, Aluminum Boat Barrier Coat, Halcyon, Elixir

---

## PERSONAL SAFETY:

Always use proper Personal Protective Equipment when handling this product. Refer to the TotalBoat Special Brushing Thinner 100 Safety Data Sheet for more info.

---

## WARNING!

RAGS, STEEL WOOL, OR WASTE SOAKED WITH THIS PRODUCT MAY SPONTANEOUSLY CATCH FIRE IF DISCARDED IMPROPERLY. IMMEDIATELY AFTER USE, PLACE RAGS, STEEL WOOL, OR WASTE IN A SEALED, WATER-FILLED METAL CONTAINER.

---

## BRUSHING and ROLLING APPLICATION

Directly before applying product, add TotalBoat Special Brushing Thinner 100 to product slowly and carefully to avoid spillage. Mix into product thoroughly until desired viscosity is reached.

- For most applications, adding up to 10% Special Brushing Thinner 100 will extend the working time, wet edge time, flow, and self-leveling properties of TotalBoat coatings.
- It is recommended to start with the least amount of Special Brushing Thinner 100 and more product little by little until the desired viscosity and feel is achieved.
- Thinning more than a product specifies may result in reduced gloss, sags, drips, excessive dry times, or an overall poor coating performance.

### Cold Weather Brushing and Rolling Applications:

TotalBoat Special Brushing Thinner 100 can be used at any temperature range. However, it may be advantageous to use TotalBoat Spray Thinner 101 for cold weather (under 60°F) brushing and rolling applications to prevent excessive dry times. Spray Thinner 101 provides excellent flow properties when used as a proprietary cold weather brushing or rolling thinner for the associated TotalBoat paints, primers, and varnishes.

---

## TOOL AND EQUIPMENT CLEANUP

TotalBoat Special Brushing Thinner 100 works as a product cleaner or tool/ equipment cleaner when used with any of the compatible TotalBoat products.

---

## SURFACE PREPARATION SOLVENT WIPE

TotalBoat Special Brushing Thinner 100 can also function as a surface preparation solvent wipe prior to applying compatible TotalBoat products.

- Only use this product as a solvent wipe when the substrate is compatible or cured sufficiently to be in contact with this product.
- Only use clean, lint-free cotton rags for solvent wipe applications.
- Change out rags frequently.



# TOTALBOAT SPECIAL BRUSHING THINNER 100

## PHYSICAL DATA:

<b>Solvent Type:</b>	Slow evaporating
<b>Storage:</b>	Store in a cool, dry area away from flames or heat sources. Store locked up. Ensure that the cap is properly tightened.
<b>Density:</b>	7.28 lbs./gallon
<b>Flash Point:</b>	96.8°F
<b>Units:</b>	Quart, Gallon
<b>VOC Content:</b>	Less than 865 g/L

## APPLICATION DATA:

<b>Type of Thinner:</b>	General purpose brushing and rolling thinner, surface preparation solvent, tool cleanup (only for compatible products).
<b>Mix Percentage:</b>	Brushing/rolling: 5-10% by volume *
	* Recommended percentage may vary across products and applications. Do not exceed the maximum recommended.
<b>Coverage:</b>	1 quart of thinner yields enough solvent to thin more than 2 gallons of compatible paint, primer, or varnish. **
	**Actual coverage will vary based on ambient conditions, products, and application techniques.
<b>Application Temperature:</b>	Brushing/Rolling: 40-100°F (TotalBoat Spray Thinner 101 may preferable under 60°F to avoid excessively long dry times).